



FASTERHOLT FM 4550/4550H



Fasterholt Maskinfabrik is the world's leading manufacturer of self-moving irrigation machines.



Straight out and in soft curves

One of the great advantages with self-moving irrigation machines from Fasterholt Maskinfabrik is, that they cannot only irrigate in straight tracks, but also in soft curves.



Belt drive is standard

The FM 4550 is fitted as standard with a belt drive for winding up the hose, but the machine can also be supplied with a hydraulic drive on the drum for winding up the hose.



Traffic lights are standard

All Fasterholt machines are today, as standard, equipped with traffic lights. Reflectors are optional equipment.



Only three 90° bends

This machine is equipped with an overpressure stop (can be equipped with underpressure). Also visible is the valve and electric motor for by-pass for speed regulation. Note that the water must only pass through three 90° bends before it comes out of the cannon.

Technical data for FM 4550 / 4550H:

Size of hose: Total length: Length without	max 675 m/100 mm – max 550 m/110 mm 8.30 m				
pull:	6.00 m				
Height	3.65 m				
Total weight without water:	4,444 kg / 4,704 kg (H model)				
Wheel gauge:	middle-middle: 1.80/2.00 m				
Size of wheels	rear wheel: 12.4"x36"x10 PR front wheel: 13.0"/75x16"/10 PR				

	 Dealer:			
mm				