

BORDING HOSE REEL IRRIGATORS

**MODEL
5TT₂ /
5TT₂ XL**



Fasterholt Maskinfabrik · Ejstrupvej 22 · Fasterholt · DK-7330 Brande
Tel. +45 9718 8066 · www.fasterholt.dk



This machine is equipped with fork drawbar, but it can also be mounted with hitch eye pull. Notice the control valve for the hydraulic turning disc, support legs and gun wagon lift.



The hydraulic turning disc can be mounted as extra equipment. An oil motor provides secure and stable turning of the machine. A separate lock prevent unnecessary turning of the machine. The hydraulic hoses are hidden into the chassis, and the valve to both turning disc and support legs are placed on the chassis.



The worm axle is placed behind the front hose guide. This is supplied with an easy changeable guider in order to prevent the worm axle from wearing out. The hose guide is directly connected to the 3 stop safety system though the worm axle.



Boogie wheels to the gun wagon are extra equipment.



All mechanical and electric parts and instructions are placed in a locker. A gas cylinder opens and closes the locker in order to protect the items from water and sunlight. The gearbox has 4 speed ranges for optimum power transfer from the turbine, and is mounted with PTO to in pull through the tractor's power transmission shaft. The turbine has been very well tested and will run for many years without problems. It is possible to attach the feed hose from both sides. Notice also the sun cells for recharging of the battery.

Technical data:

Size of hose:	90 mm up to 400 m 90 mm up to 440 m 100 mm up to 350 m 100 mm up to 400 m 100 mm up to 450 m
Size of wheels:	10/75x15
Wheels for gun wagon:	5" x 8"
Length without gun wagon:	4,00 m
Width:	2,30 m
Height:	3,20 m
Max weight without water:	2.850 kg

5TT2 / 5TT2XL

Dealer:

Manufacturer:

Fasterholt Maskinfabrik A/S · DK-7330 Brande · Tel. +45 9718 8066
www.fasterholt.dk